

## ID-Nr. 32936-001 Model SLX.230.120.MV



Dimensions	
Width (external)	1197.00 mm
Depth (external)	615.00 mm
Height (external)	2300.00 mm
Width (internal)	485.00 mm
Depth (internal)	565.00 mm
Height (internal)	1865.00 mm
The available internal dimensions can vary depend	ding on the interior equipment package

The available internal dimensions can vary depending on the interior equipment package.

195 kg
204.00 kg/m <sup>2</sup>
300 kg

Electrical component	
Frequency	50 Hz
Nominal voltage	230 V
Maximum current consumption	0.5 A
Power consumption in operation	120 W
Power consumption in standby mode	50 W

Colouring / Surface finish	
Body colour code	RAL 7035
Body colour	light grey
Body surface finish	plain
Door / Drawer colour code	RAL 7035
Door / Drawer colour	light grey
Door / Drawer surface finish	plain

General Information	
Number of doors	2
Depth with open doors	1153 mm
Customs tariff number	94032080









Recirculating air filter storage cabinet SLX-CLASSIC Model SLX.230.120.MV, light grey (RAL 7035)

Safe and approved storage of aggressive, non flammable hazardous materials in workrooms

## **Function / construction:**

## **Cabinet body**

- Robust construction and longevity: cabinet body made of powder-coated sheet steel, safety elements assembled outside the storage compartment for increased protection against corresion
- **Two in one:** two hermetically separated storage compartments allow the isolated storage of acids and bases in one cabinet
- **No unauthorised use:** doors lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor

## **Recirculating air filter system**

- Ideal for the direct installation in working areas very low noise, only approx. 39 dB (A)
- With multi-stage wideband filter
- Monitoring electronics for extraction incl. cool-device cable and power plug
- Optical and acoustical alarm including potential-free alarm
  contact
- Display with innovative touch panel
- Manual check of the filter saturation

Front view Side view





